State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-21-206

Relating to Certification of New Heavy-Duty Engines and Vehicles

CUMMINS ENGINE COMPANY, INC.

Pursuant to the authority vested in the Air Resources Board by Sections 43100, 43102 and 43103 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following 1998 model-year Cummins Engine Company, Inc. diesel-cycle engines are certified for use in motor vehicles with a manufacturer's gross vehicle weight rating (GVWR) over 14,000 pounds:

<u>Fuel Type</u>: Diesel

Engine Family	Engine Displacement Liters (Cubic Inches)		Exhaust Emission Control Systems and Special Features	
WCEXH0359BAD (403J)	5.9	(359)	Turbocharger Charge Air Cooler Powertrain Control Module	

Engine models and codes are listed on attachments.

The following are the certification exhaust emission standards for this engine family in grams per brake horsepower-hour:

Total	Carbon	Nitrogen	<u>Particulates</u>
<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	
1.3	15.5	4.0	0.10

The following are the certification exhaust emission values for this engine family in grams per brake horsepower-hour:

Total	Carbon	Nitrogen	<u>Particulates</u>
<u>Hydrocarbons</u>	<u>Monoxide</u>	Oxides	
0.1	0.8	4.0	0.09

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

BE IT FURTHER RESOLVED: That the aforementioned engine family has been conditionally certified subject to the following conditions:

- 1. Any engine which employs a defeat device shall not be covered by this Executive Order.
- 2. Within 90 days following the issuance of this Executive Order, the manufacturer must show cause, to the satisfaction of the Executive Officer or his designee, that the strategy for fuel injection timing, including timing during the fuel economy mode, is not a defeat device.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachments.

Executed at El Monte, California this 26 day of February 1998.

R. B. Summerfield, Chief

Mobile Source Operations Division

LARGE ENGINE MODEL SUMMARY

Process Code: New Submission Manufacturer: Cummins Engine Company, Inc.

EPA Engine Family: WCEXH0359BAD

Manufacturer Family Name:

403J

PCM, TC, CAC

99

123

660@1600

8.Fuel Rate: 9.Emission Control (lbs/hr)@peak torque Device Per SAE J1930

7.Fuet Rate: mm/stroke@peak torque

6.Torque @ RPM (SEA Gross)

5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)

4.Fuel Rate: mrr/stroke @ peak HP (for diesel only)

3.BHP@RPM (SAE Gross)

2.Engine Model 1.Engine Code CPL2451

ISB 275 FR90152

275@2400

124

100